CARRYALL 252

UTILITY VEHICLES





UTILITY VEHICLES

PERFORMANCE FEATURES

- Lightweight, rust-proof aluminum frame
- Smooth riding front and rear suspension
- Tightest turning diameter in class (5.3 m)
- Greatest operating range (26.5 L fuel tank)
- · Self-adjusting rack and pinion steering

O = Optional Field-installed Equipment

√ = Standard Equipment

- Self-adjusting rear mechanical drum brakes with foot-operated park brake
- Choice of gas or electric powertrain
- Generous 0.2 m³, 136.1 kg bed box capacity •
- 362.9 kg total vehicle capacity
- · 2 year, 2000 hour limited warranty
- Durable, corrosion-resistant, composite bed box
- · Spacious floor-mat covered foot well
- Scratch and impact resistant ABS Plastic front and ArmorFlex® rear body
- · Available in red or green





| STANDARD EQUIPMENT | ELECTRIC | GASOLINE |
|---|--|--|
| Gasoline Engine | NA | Kawasaki 9.5 hp, 286cc |
| Electric Motor | 48-volt, 10 hp intermittent | NA |
| Reverse Warning Indicator | ✓ | ✓ |
| Headlights | ✓ | ✓ |
| 3-cup Beverage Holder | ✓ | ✓ |
| Fuel Gauge/Hour Meter/Oil Light | NA | \checkmark |
| State of Charge Indicator/Battery Light | ✓ | NA |
| Front Impact Protection | Cast Steel Bumper | Cast Steel Bumper |
| 12-volt Accessory Plug | 0 | 0 |
| Wheels | Gray Steel Rims | Gray Steel Rims |
| Dash Storage | Dash Pocket | Dash Pocket |
| Differential Guard | 0 | 0 |
| SPECIFICATIONS | | |
| Maximum Speed | 27.4-30.6 kph (17-19 mph) | 27.4-30.6 kph (17-19 mph) |
| Vehicle Dimensions (I x w x h) | 255.3 x 125.7 x 121.9 cm (100.5 x 49.5 x 48 in.) | 255.3 x 125.7 x 121.9 cm (100.5 x 49.5 x 48 in.) |
| Curb Weight (less battery and fuel) | 396.4 kg (874 lb.) | 354.3 kg (781 lb.) |
| Wheelbase | 165.1 cm (65 in.) | 165.1 cm (65 in.) |
| Ground clearance under differential | 14.0 cm (5.5 in.) | 14.0 cm (5.5 in.) |
| Cargo box dimensions (I x w x h) | 65.3 x 110.5 x 27.9 cm (25.7 x 43.5 x 11 in.) | 65.3 x 110.5 x 27.9 cm (25.7 x 43.5 x 11 in.) |
| Tread (front/rear) | 86.4/96.5 cm (34/38 in.) | 86.4/96.5 cm (34/38 in.) |
| Tires | 20 x 1000 - 8, 4-ply rated, All-trail II | 20 x 1000 - 8, 4-ply rated, All-trail II |
| Front Suspension | Independent leaf spring with | Independent leaf spring with |
| | dual hydraulic shocks | dual hydraulic shocks |
| Rear Suspension | Leaf springs w/ dual hydraulic shocks | Leaf springs w/ dual hydraulic shocks |
| | | |

ACCESSORIES



and Canopy

Split Windshield











Brush Guard


Nerf Bars

Sport Wheel Covers

Taillights

Trailer Hitch & Ball

Locking Glove Box



PO BOX 204658 • AUGUSTA, GA 30917-4658 Phone 1-800-Club Car/1-706-863-3000 • www.clubcar.com

